

## **TECHNICAL DATA**

## SHARP 100 36V/170A BATTERY CHARGERS

OTATED DATA ACCORDING TO MICROSCOVER	CTANDADD
STATED DATA ACCORDING TO MICROPOWER	( 21ANDAKD
Part number	SS3566
Model	SHARP 100
Туре	36V/170A
MAINS DATA (50/60HZ)	
Output Voltage [V]	36
Output Current [A]	170
Number of phases	3
Rated Voltage range [V]	-
Current at nominal voltage [A]	10.3
Recommended supply fuse [A]	16
Supply cable area	4xAWG14
Supply cable length [m]	3
Typical Supply Connector	L16-20P
Output cable cross-section	1/0 AWG
BATTERY CONNECTION	
Output cable cross-section	1/0 AWG
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	36
ELECTRIC DATA	
Standby Power Consumption [W]	<10
Power Consumption [W]	8108
Apparent Power Consumption [VA]	8535

Printout date: 2025-01-30

utput Ripple	B <5
utput Ripple	<5
fficiency (at rated power and no cables) [%]	92
ROPERTIES	
ngress protection	IP20
mbient temperature range (at full output power) [deg C]	-5 to +40
mbient max temp (with reduced output power) [deg C]	50
ooling	Convection
hort Circuit Protection	Yes
rong Polarity Protection	Fuse
abinet Type	\$18
ertifications	UL
MI	LED
MI Language	-
eporting	No
adio Communication	No
harging Curve Set	10-04,06,18 & 20-09
O-cards	No
E	No
L	Yes
CHARGING TIMES	
Hours cap.ah/5h	976
Hours cap.ah/5h	1415
D Hours cap.ah/5h	1888
2 Hours cap.ah/5h	2266
CHARGER DIMENSIONS	
/eight excl. cables [kg]	16
/eight incl. cables [kg]	22
uter Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	25
Box Height [mm]	650
Box Width [mm]	370
Box Depth [mm]	440
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-lon	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No