MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

TECHNICAL DATA

SHARP 20 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	924324
Model	SHARP 20
Type	36V/20A

MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	20
Mains Phase	1
Input Voltage [V]	220-240
Max Mains Current (at nominal mains V) [A]	4,3
Recommended Mains Fuse [A]	10
Mains Cable Area [mm2]	3x1,5
Mains Cable Length [m]	2,5
Mains Connector	10A Schuko
Battery Cable [mm2]	2x6

BATTERY CONNECTION

Battery Cable [mm2]	2x6
Battery Cable Connection (in charger)	Terminal
Battery Cable Length [m]	2
Battery Connector (not included)	User defined
Output Voltage [V]	36

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	980
Apparent Power Consumption [VA]	990

Power Factor	0,99
Inrush Current [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	89

PROPERTIES

IP Protection	IP20
Operation Temperature [deg C]	-5 to +40
Ambient Max Temperature (with reduced capacity) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Electronic
Cabinet Type	P4
Certifications	
HMI	LED
HMI Language	-
Bluetooth/ NFC connectivity	No
Remote connectivity & advanced software functions	No
Charging Curve Set	10-04,06 & 20-09
I/O-cards	No
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	102
8 Hours cap.ah/5h	153
10 Hours cap.ah/5h	209
12 Hours cap.ah/5h	266

CHARGER DIMENSIONS

Charger Weight excl. Cables [kg]	
Charger Weight incl. Cables [kg]	
Outer Dimensions Height [mm]	243

Outer Dimensions Width [mm]	112
Outer Dimensions Depth [mm]	74
Min Spacing Required	150

SHIPPING DIMENSIONS

Shipping Weight [kg]	2
Box Height [mm]	310
Box Width [mm]	200
Box Depth [mm]	140

CHARGING

Charging Ionic	LK10-04 Chemical Acid Circulation (Ionic)
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.

Micropower Group
Gulhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se