

TECHNICAL DATA

DC-DC CONVERTER ISOLATED DC-DC CONVERTERS & CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|--------------------------|
| Part number | 0060317 |
| Model | DC-DC Converter Isolated |
| Type | 9-36/24 Wide input |

MAINS DATA (50/60HZ)

| | |
|--------------------------------|----|
| Output Voltage [V] | 24 |
| Output Current [A] | |
| Number of phases | |
| Rated Voltage range [V] | |
| Current at nominal voltage [A] | |
| Recommended supply fuse [A] | |
| Supply cable area | |
| Supply cable length [m] | |
| Typical Supply Connector | |
| Output cable cross-section | |

BATTERY CONNECTION

| | |
|----------------------------------|----|
| Output cable cross-section | |
| Output cable terminals (in unit) | |
| Output cable length [m] | |
| Typical Output connector | |
| Output Voltage [V] | 24 |

PROPERTIES

| | |
|--|------|
| Ingress protection | IP21 |
| Ambient temperature range (at full output power) [deg C] | |

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting

Radio Communication

Charging Curve Set

I/O-cards

CE

UL

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.