

TECHNICAL DATA

ACCESS 200 80V/200A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	MA6627
Model	ACCESS 200
Type	80V/200A

MAINS DATA (50/60HZ)

Output Voltage [V]	80
Output Current [A]	200
Number of phases	3
Rated Voltage range [V]	600-600
Current at nominal voltage [A]	21,1
Recommended supply fuse [A]	25
Supply cable area	4xAWG10
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2xAWG2/0

BATTERY CONNECTION

Output cable cross-section	2xAWG2/0
Output cable terminals (in unit)	M10
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	80

ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	20817
Apparent Power Consumption [VA]	21913

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	93

PROPERTIES

Ingress protection	IP20
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A7
Certifications	
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	Yes
I/O-cards	Multiple
CE	No
UL	Yes

CHARGING TIMES

6 Hours cap.ah/5h	
8 Hours cap.ah/5h	1149
10 Hours cap.ah/5h	1665
12 Hours cap.ah/5h	2221

CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	659

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	445
Min Spacing Required	300

SHIPPING DIMENSIONS

Shipping Weight [kg]	44
Box Height [mm]	560
Box Width [mm]	360
Box Depth [mm]	820

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.