

## TECHNICAL DATA

# ACCESS 100 48V/165A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |            |
|-------------|------------|
| Family      | ACCESS 100 |
| DC Rating   | 48V/165A   |
| Part number | AR4551     |
| Model code  | 1AA7503    |
| Part status | Released   |

### SUPPLY

|                                               |                       |
|-----------------------------------------------|-----------------------|
| Number of phases                              | 3                     |
| Rated Voltage range [V]                       | 380-415               |
| Nominal Voltage [V]                           | 400                   |
| Rated frequency [Hz]                          | 50-60                 |
| Current at nominal voltage [A]                | 15,7                  |
| Current at min rated voltage [A]              | 16                    |
| Current at max rated voltage [A]              | 15,2                  |
| Recommended supply fuse class                 | C                     |
| Recommended RCCB class                        | B                     |
| Supply cable area                             | 4x2,5 mm <sup>2</sup> |
| Supply cable length [m]                       | 12,5                  |
| Typical Supply Connector                      | CEE16                 |
| Standby Power Consumption [W]                 | <10                   |
| Power Consumption [W]                         | 10336                 |
| Apparent Power Consumption [VA]               | 10880                 |
| Power Factor                                  | 0,95                  |
| Leakage current [mA]                          | <3,5                  |
| Efficiency (at rated power and no cables) [%] | 93                    |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 48                      |
| Output Current [A]               | 165                     |
| Output cable cross-section       | 50 mm <sup>2</sup>      |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M8                      |
| Typical Output connector         | DIN320                  |
| Output fuse, rating [A/VDC]      | 200A/150VDC             |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|                                                      |                  |
|------------------------------------------------------|------------------|
| Ingress protection                                   | IP20             |
| Operation Temperature [deg C]                        | -5 to +40        |
| Ambient max temp (with reduced output power) [deg C] | 50               |
| Ambient storage and transport temperature [C]        | -40 to +80/1000h |
| Maximum operating altitude [m]                       | 2000             |
| Maximum humidity, non-condensing [%]                 | 90               |
| Cooling                                              | Fan              |
| Cabinet Type                                         | A17              |
| Certifications                                       | CE               |
| Cloud connection                                     | Yes              |
| User interface                                       | LED/Display      |
| Charging Curve Set                                   | Multiple Lead    |
| I/O-cards                                            | Optional         |
| Reporting                                            | Yes              |
| Radio communication                                  | Yes              |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 14          |
| Charger dimensions [mm]  | 417x256x243 |

SHIPPING DIMENSIONS

|                      |             |
|----------------------|-------------|
| Box dimensions [mm]  | 465x365x525 |
| Shipping Weight [kg] | 21          |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*