MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

# TECHNICAL DATA

# MICROPOWER SL260 PB 120V/180A BATTERY CHARGERS

## STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|---|---|
| Family | SL260 |
| DC Rating | 120V/180A |
| Part number | DB7586-B3/0 |
| Model code | 1A5B2AP |
| Part status | Released |

## SUPPLY

| | |
|---|---|
| Mains Phase | 3 |
| Input Voltage [V] | 480 |
| Nominal Voltage [V] | 480 |
| Rated frequency [Hz] | 50-60 |
| Max Mains Current (at nominal mains V) [A] | 34,1 |
| Current at min rated voltage [A] | 34,1 |
| Current at max rated voltage [A] | 34,1 |
| Recommended supply fuse class | C |
| Recommended RCCB class | B |
| Mains Cable Area [mm2] | 4xAWG6 |
| Mains Cable Length [m] | □2.5 |
| Mains Connector | L16-60P |
| Standby Power Consumption [W] | <3,5 |
| Power Consumption [W] | 27076 |
| Apparent Power Consumption [VA] | 28293 |
| Power Factor | 0,96 |
| Leakage current [mA] | <3,5 |
| Efficiency (at rated power and no cables) [%] | 96 |

## OUTPUT DATA

| | |
|---|---|
| Reversed polarity protection | Fuse |
| Short Circuit Protection | Yes |
| Output Voltage [V] | 120 |
| Output Current [A] | 180 |
| Battery Cable [mm2] | 2/0 AWG |
| Battery Cable Length [m] | 3 |
| Battery Cable Connection (in charger) | M8 |
| Battery Connector (not included) | DIN320 |
| Output fuse, rating [A/VDC] | 2x125A/150VDC |
| Output fuse type | Fast Semiconductor fuse |

## PROPERTIES

| | |
|---|---|
| IP Protection | IP21 |
| Operation Temperature [deg C] | -5 to +40 |
| Ambient Max Temperature (with reduced capacity) [deg C] | 50 |
| Ambient storage and transport temperature [C] | -40 to +80/1000h |
| Maximum operating altitude [m] | 2000 |
| Maximum humidity, non-condensing [%rh] | 90 |
| Cooling | Fan |
| Cabinet Type | B2 |
| Certifications | UL |
| Cloud connection | Yes |
| User interface | LED/Display |
| Charging Curve Set | Multiple Lead |
| I/O-cards | Remote Start/Stop |
| Bluetooth/ NFC connectivity | Yes |
| Remote connectivity & advanced software functions | Yes |

## CHARGER DIMENSIONS

| | |
|---|---|
| Charger Weight excl. Cables [kg] | 42 |
| Charger dimensions [mm] | 410x533x515 |

## SHIPPING DIMENSIONS

| | |
|---|---|
| Box dimensions [mm] | 560x800x600 |
| Shipping Weight [kg] | 64 |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*

Micropower Group
Gullhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se

Printout date: 2026-11-22