

## TECHNICAL DATA

# PAC/PAP 800UL 800W 36/20 BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|                                  |                     |
|----------------------------------|---------------------|
| Part number                      |                     |
| Model                            | PAC/PAP 800UL 800W  |
| Type                             | 36V/20A Fan Cooling |
| MAINS DATA (50/60HZ)             |                     |
| Output Voltage [V]               | 36                  |
| Output Current [A]               | 20                  |
| Number of phases                 |                     |
| Rated Voltage range [V]          | 55-140              |
| Current at nominal voltage [A]   |                     |
| Recommended supply fuse [A]      |                     |
| Supply cable area                |                     |
| Supply cable length [m]          |                     |
| Typical Supply Connector         |                     |
| Output cable cross-section       |                     |
| BATTERY CONNECTION               |                     |
| Output cable cross-section       |                     |
| Output cable terminals (in unit) |                     |
| Output cable length [m]          |                     |
| Typical Output connector         |                     |
| Output Voltage [V]               | 36                  |
| ELECTRIC DATA                    |                     |
| Standby Power Consumption [W]    |                     |
| Power Consumption [W]            |                     |
| Apparent Power Consumption [VA]  |                     |

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple

Efficiency (at rated power and no cables) [%]

PROPERTIES

Ingress protectionIP20

Operation Temperature [deg C]

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

ReportingNo

Radio CommunicationNo

Charging Curve Set

I/O-cards

CENo

ULYes

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg]

Outer Dimensions Height [mm]

Outer Dimensions Width [mm]

Outer Dimensions Depth [mm]

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.