

TECHNICAL DATA

ACCESS 200 36V/410A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AU3874
Model	ACCESS 200
Type	36V/410A

MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	410
Number of phases	3
Rated Voltage range [V]	440-440
Current at nominal voltage [A]	28,1
Recommended supply fuse [A]	32
Supply cable area	4x6
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2x2xAWG3/0(High temp)

BATTERY CONNECTION

Output cable cross-section	2x2xAWG3/0(High temp)
Output cable terminals (in unit)	M10
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	36

ELECTRIC DATA

Standby Power Consumption [W]	<15
Power Consumption [W]	20348
Apparent Power Consumption [VA]	21419

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A22
Certifications	
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	Yes
I/O-cards	Multiple
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	
8 Hours cap.ah/5h	2355
10 Hours cap.ah/5h	3417
12 Hours cap.ah/5h	4561

CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	659

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	459
Min Spacing Required	300

SHIPPING DIMENSIONS

Shipping Weight [kg]	51
Box Height [mm]	560
Box Width [mm]	360
Box Depth [mm]	820

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.