

## TECHNICAL DATA

# SHARP 100 80V/40A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SR6301
Model	SHARP 100
Type	80V/40A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	80
Output Current [A]	40
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	6.3
Recommended supply fuse [A]	10
Supply cable area	4x1,5 mm <sup>2</sup>
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	10 mm <sup>2</sup>

#### BATTERY CONNECTION

Output cable cross-section	10 mm <sup>2</sup>
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	80

#### ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	4112
Apparent Power Consumption [VA]	4329

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	94

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	S17
Certifications	CE
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]	14
Weight incl. cables [kg]	16
Outer Dimensions Height [mm]	417

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	Se User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	18
Box Height [mm]	465
Box Width [mm]	365
Box Depth [mm]	525

## CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*