

TECHNICAL DATA

MICROPOWER SL370 PB 120V/260A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	DC7729
Model	Micropower SL390
Type	120V/260A

MAINS DATA (50/60HZ)

Output Voltage [V]	120
Output Current [A]	260
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	59,4
Recommended supply fuse [A]	63
Supply cable area	4x16 mm ²
Supply cable length [m]	22,5
Typical Supply Connector	CEE63
Output cable cross-section	95 mm ²

BATTERY CONNECTION

Output cable cross-section	95 mm ²
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	120

ELECTRIC DATA

Standby Power Consumption [W]	<3,5
Power Consumption [W]	39346
Apparent Power Consumption [VA]	41114

Power Factor	0,96
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	96

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	B3
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple Lead
I/O-cards	Remote Start/Stop
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	1492
8 Hours cap.ah/5h	2163
10 Hours cap.ah/5h	2889
12 Hours cap.ah/5h	3468

CHARGER DIMENSIONS

Weight excl. cables [kg]	56
Weight incl. cables [kg]	66
Outer Dimensions Height [mm]	699

Outer Dimensions Width [mm]	579
Outer Dimensions Depth [mm]	520
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	81
Box Height [mm]	670
Box Width [mm]	800
Box Depth [mm]	600

CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No