

## TECHNICAL DATA

# MICROPOWER SX14 PB 24V/50A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	WG2320
Model	Micropower SX14
Type	24V/50A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	50
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	7,2
Recommended supply fuse [A]	10
Supply cable area	3x1,5 mm <sup>2</sup>
Supply cable length [m]	2,3
Typical Supply Connector	Fixed or IEC C19/CEE17
Output cable cross-section	16 mm <sup>2</sup>

#### BATTERY CONNECTION

Output cable cross-section	16 mm <sup>2</sup>
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	24

#### ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1613
Apparent Power Consumption [VA]	1646

Power Factor	0,98
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A51
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple Lead
I/O-cards	Basic
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h	255
8 Hours cap.ah/5h	383
10 Hours cap.ah/5h	523
12 Hours cap.ah/5h	605

## CHARGER DIMENSIONS

Weight excl. cables [kg]	6
Weight incl. cables [kg]	8
Outer Dimensions Height [mm]	455

Outer Dimensions Width [mm]	220
Outer Dimensions Depth [mm]	103
Min Spacing Required	See User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	9
Box Height [mm]	165
Box Width [mm]	265
Box Depth [mm]	595

## CHARGING

Charging Ionic	LK-10-04
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*