

## TECHNICAL DATA

# MICROPOWER SL230 PB 48V/400A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower SL230
DC Rating	48V/400A
Part number	DE4866-B3/0
Model code	1A5B4DK
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	31
Current at min rated voltage [A]	31
Current at max rated voltage [A]	31
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG8
Supply cable length [m]	2.5
Typical Supply Connector	L16-50P
Standby Power Consumption [W]	<3,5
Power Consumption [W]	24641
Apparent Power Consumption [VA]	25775
Power Factor	0,96
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	95

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	400
Output cable cross-section	4/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN640
Output fuse, rating [A/VDC]	3x200A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	B4
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Remote Start/Stop
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	64
Charger dimensions [mm]	699x579x520

## SHIPPING DIMENSIONS

Box dimensions [mm]

845x800x600

Shipping Weight [kg]

95

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*