

TECHNICAL DATA

ACCESS 100 36V/130A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	ACCESS 100
DC Rating	36V/130A
Part number	AS3483
Model code	1AA7705
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	208-240
Nominal Voltage [V]	208
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	18,3
Current at min rated voltage [A]	18,3
Current at max rated voltage [A]	15,8
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4x4 mm ²
Supply cable length [m]	□2.5
Typical Supply Connector	GEE32
Standby Power Consumption [W]	<10
Power Consumption [W]	6246
Apparent Power Consumption [VA]	6574
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	91

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	36
Output Current [A]	130
Output cable cross-section	50 mm ²
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A18
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Optional
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	16
Charger dimensions [mm]	529x256x244

SHIPPING DIMENSIONS

Box dimensions [mm]	650x370x440
Shipping Weight [kg]	23

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.