

## TECHNICAL DATA

# MICROPOWER SL170 LI 36V/400A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	EB3866
Model	Micropower SL170
Type	36V/400A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	400
Number of phases	3
Rated Voltage range [V]	-
Current at nominal voltage [A]	24.0
Recommended supply fuse [A]	tbd
Supply cable area	4xAWG10
Supply cable length [m]	> 2,5
Typical Supply Connector	tbd
Output cable cross-section	250 KCMIL

#### BATTERY CONNECTION

Output cable cross-section	250 KCMIL
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	-
Output Voltage [V]	36

#### ELECTRIC DATA

Standby Power Consumption [W]	< 10
Power Consumption [W]	18925
Apparent Power Consumption [VA]	19921

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	93

## PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	B2
Certifications	UL
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	No
UL	Yes

## CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]	42
Weight incl. cables [kg]	52
Outer Dimensions Height [mm]	415

Outer Dimensions Width [mm]	579
Outer Dimensions Depth [mm]	520
Min Spacing Required	See User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	66
Box Height [mm]	560
Box Width [mm]	800
Box Depth [mm]	600

## CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*