

## TECHNICAL DATA

# MICROPOWER ST100 LI 36V/220A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower ST100
DC Rating	36V/220A
Part number	LV3669-B1
Model code	1AA8052
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	15.7
Current at min rated voltage [A]	16.0
Current at max rated voltage [A]	14.2
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4x2.5 mm <sup>2</sup>
Supply cable length [m]	□2.5
Typical Supply Connector	GEE16
Standby Power Consumption [W]	<5
Power Consumption [W]	10296
Apparent Power Consumption [VA]	10838
Power Factor	0.95
Leakage current [mA]	<3.5
Efficiency (at rated power and no cables) [%]	93

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	36
Output Current [A]	220
Output cable cross-section	95 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	300A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A19
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	18
Charger dimensions [mm]	571x270x258

## SHIPPING DIMENSIONS

Box dimensions [mm]	425x380x690
Shipping Weight [kg]	28

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*