

## TECHNICAL DATA

# DC-DC CONVERTER ISOLATED 12-24 DC-DC CONVERTERS & CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	HA2261-D10101-01
Model	DC-DC Converter Isolated
Type	12-24

#### MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	
Number of phases	
Rated Voltage range [V]	
Current at nominal voltage [A]	
Recommended supply fuse [A]	
Supply cable area	
Supply cable length [m]	
Typical Supply Connector	
Output cable cross-section	

#### BATTERY CONNECTION

Output cable cross-section	
Output cable terminals (in unit)	
Output cable length [m]	
Typical Output connector	
Output Voltage [V]	24

#### PROPERTIES

Ingress protection	IP67
Ambient temperature range (at full output power) [deg C]	

Ambient max temp (with reduced output power) [deg C]

---

Cooling

---

Short Circuit Protection

---

Wrong Polarity Protection

---

Cabinet Type

---

Certifications

---

HMI

---

HMI Language

---

Reporting

---

Radio Communication

---

Charging Curve Set

---

I/O-cards

---

CE

---

UL

---

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*