

TECHNICAL DATA

LION 100 24V/150A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LS2524
Model	LION 100
Type	24V/150A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	150
Number of phases	3
Rated Voltage range [V]	440-440
Current at nominal voltage [A]	6.7
Recommended supply fuse [A]	10
Supply cable area	4x1,5 mm ²
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	50 mm ²

BATTERY CONNECTION

Output cable cross-section	50 mm ²
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	< 10
Power Consumption [W]	4846
Apparent Power Consumption [VA]	5101

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A18
Certifications	CE
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Yes
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	16
Weight incl. cables [kg]	20
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	244
Min Spacing Required	Se User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	23
Box Height [mm]	650
Box Width [mm]	370
Box Depth [mm]	440

CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.