

## TECHNICAL DATA

# SHARP 20 BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	924330
Model	SHARP 20
Type	36V/40A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	40
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	8,6
Recommended supply fuse [A]	10
Supply cable area	3x1,5
Supply cable length [m]	2,5
Typical Supply Connector	10A Schuko
Output cable cross-section	2x10

#### BATTERY CONNECTION

Output cable cross-section	2x10
Output cable terminals (in unit)	M6
Output cable length [m]	2
Typical Output connector	User defined
Output Voltage [V]	36

#### ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1967
Apparent Power Consumption [VA]	1987

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	89

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Electronic
Cabinet Type	P6
Certifications	
HMI	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	10-04,06 & 20-09
I/O-cards	No
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h	204
8 Hours cap.ah/5h	306
10 Hours cap.ah/5h	418
12 Hours cap.ah/5h	532

## CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	295

Outer Dimensions Width [mm]	138
Outer Dimensions Depth [mm]	89
Min Spacing Required	150

## SHIPPING DIMENSIONS

Shipping Weight [kg]	3
Box Height [mm]	390
Box Width [mm]	250
Box Depth [mm]	140

## CHARGING

Charging Ionic	LK10-04 Chemical Acid Circulation (Ionic)
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*