

TECHNICAL DATA

MICROPOWER SC11 PB 24V/40A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|-----------------|
| Family | Micropower SC11 |
| DC Rating | 24V/40A |
| Part number | VA2300 |
| Model code | 3AFD110 |
| Part status | Released |

SUPPLY

| | |
|---|-----------------------|
| Number of phases | 1 |
| Rated Voltage range [V] | 220-240 |
| Nominal Voltage [V] | 230 |
| Rated frequency [Hz] | 50-60 |
| Current at nominal voltage [A] | 5.7 |
| Current at min rated voltage [A] | 6 |
| Current at max rated voltage [A] | 5.5 |
| Recommended supply fuse class | C |
| Recommended RCCB class | A |
| Supply cable area | 3x1,0 mm ² |
| Supply cable length [m] | 2,3 |
| Typical Supply Connector | IEC C14/CEE17 |
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 1294 |
| Apparent Power Consumption [VA] | 1320 |
| Power Factor | 0.98 |
| Leakage current [mA] | <3,5 |
| Efficiency (at rated power and no cables) [%] | 91 |

OUTPUT DATA

| | |
|----------------------------------|-------------------------|
| Reversed polarity protection | Fuse |
| Short Circuit Protection | Yes |
| Output Voltage [V] | 24 |
| Output Current [A] | 40 |
| Output cable cross-section | 10 mm ² |
| Output cable length [m] | 3 |
| Output cable terminals (in unit) | - |
| Typical Output connector | DIN80 |
| Output fuse, rating [A/VDC] | 60A/150VDC |
| Output fuse type | Fast Semiconductor fuse |

PROPERTIES

| | |
|--|---------------------|
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 55 |
| Ambient storage and transport temperature [C] | -40 to +80/1000h |
| Maximum operating altitude [m] | 2000 |
| Maximum humidity, non-condensing [%rh] | 90 |
| Cooling | Convection |
| Cabinet Type | A50 |
| Certifications | CE |
| Cloud connection | No |
| User interface | LED |
| Charging Curve Set | 10-04,06,18 & 20-09 |
| I/O-cards | Basic |
| Reporting | No |
| Radio communication | No |

CHARGER DIMENSIONS

| | |
|--------------------------|-------------|
| Weight excl. cables [kg] | 3 |
| Charger dimensions [mm] | 333x150x103 |

SHIPPING DIMENSIONS

Box dimensions [mm]

135x290x390

Shipping Weight [kg]

4

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.