

TECHNICAL DATA

MICROPOWER SC14 PB 24V/50A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	VG2320
Model	Micropower SC14
Type	24V/50A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	50
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	7,2
Recommended supply fuse [A]	10
Supply cable area	3x1,0 mm ²
Supply cable length [m]	2,3
Typical Supply Connector	IEC C14/CEE17
Output cable cross-section	16 mm ²

BATTERY CONNECTION

Output cable cross-section	16 mm ²
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1613
Apparent Power Consumption [VA]	1646

Power Factor	0,98
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A50
Certifications	CE
HMI	LED
HMI Language	-
Reporting	Yes
Radio Communication	No
Charging Curve Set	10-06, 10-18, 20-09, 10-04
I/O-cards	No
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	285
8 Hours cap.ah/5h	415
10 Hours cap.ah/5h	555
12 Hours cap.ah/5h	

CHARGER DIMENSIONS

Weight excl. cables [kg]	2
Weight incl. cables [kg]	4
Outer Dimensions Height [mm]	333

Outer Dimensions Width [mm]	150
Outer Dimensions Depth [mm]	103
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	5
Box Height [mm]	135
Box Width [mm]	290
Box Depth [mm]	390

CHARGING

Charging Ionic	LK-10-18
Charging Standard	LK10-06
Charging Gel	LK20-09
Charging Li-Ion	-
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.