

## TECHNICAL DATA

# MICROPOWER SC17 PB 24V/60A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower SC17
DC Rating	24V/60A
Part number	VK2340-A1
Model code	3AFD710
Part status	Released

### SUPPLY

Number of phases	1
Rated Voltage range [V]	220-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	8.6
Current at min rated voltage [A]	9.0
Current at max rated voltage [A]	8.3
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	3x1.5 mm <sup>2</sup>
Supply cable length [m]	2.3
Typical Supply Connector	Fixed or IEC C19/CEE17
Standby Power Consumption [W]	<5
Power Consumption [W]	1942,417582
Apparent Power Consumption [VA]	1982,058758
Power Factor	0.98
Leakage current [mA]	<3.5
Efficiency (at rated power and no cables) [%]	91

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	60
Output cable cross-section	16 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	160A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Ambient storage and transport temperature [C]	-25 to +60/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A51
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	Basic option are integrated
Reporting	No
Radio communication	No

## CHARGER DIMENSIONS

Weight excl. cables [kg]	6
Charger dimensions [mm]	455x220x103

## SHIPPING DIMENSIONS

Box dimensions [mm]	165x265x595
Shipping Weight [kg]	9.1

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*