

TECHNICAL DATA

MICROPOWER SL100 PB 48V/165A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	SL100
DC Rating	48V/165A
Part number	DA4556-B3/0
Model code	1A5B2BK
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	12,8
Current at min rated voltage [A]	12,8
Current at max rated voltage [A]	12,8
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG12
Supply cable length [m]	12,5
Typical Supply Connector	L16-20P
Standby Power Consumption [W]	<3,5
Power Consumption [W]	10129
Apparent Power Consumption [VA]	10595
Power Factor	0,96
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	95

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	165
Output cable cross-section	1/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	1x200A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP21
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	90
Cooling	Convection
Cabinet Type	B2
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Remote Start/Stop
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	29
Charger dimensions [mm]	410x533x515

SHIPPING DIMENSIONS

Box dimensions [mm]	560x800x600
Shipping Weight [kg]	50

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.