

## TECHNICAL DATA

# MIL DC-DC CONVERTER ISOLATED DC-DC CONVERTERS & CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |                     |
|-------------|---------------------|
| Part number | 0060324MIL          |
| Model       | MIL DC-DC Converter |
| Type        | 24V/24V 400W        |

### MAINS DATA (50/60HZ)

|                                |    |
|--------------------------------|----|
| Output Voltage [V]             | 24 |
| Output Current [A]             |    |
| Number of phases               |    |
| Rated Voltage range [V]        |    |
| Current at nominal voltage [A] |    |
| Recommended supply fuse [A]    |    |
| Supply cable area              |    |
| Supply cable length [m]        |    |
| Typical Supply Connector       |    |
| Output cable cross-section     |    |

### BATTERY CONNECTION

|                                  |    |
|----------------------------------|----|
| Output cable cross-section       |    |
| Output cable terminals (in unit) |    |
| Output cable length [m]          |    |
| Typical Output connector         |    |
| Output Voltage [V]               | 24 |

### PROPERTIES

|                               |      |
|-------------------------------|------|
| Ingress protection            | IP67 |
| Operation Temperature [deg C] |      |

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting

Radio Communication

Charging Curve Set

I/O-cards

CE

UL

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.